## SUPER CATV INDOOR AMPLIFIER

## **MODEL: ASD-40**





## **Features:**

- Deluxe Aluminum Housing for Excellent Heat-Sinking.
- > Tilt Control & Gain Control Continuously Adjustable.
- > Easy Installation.
- ➤ Gain 40dB to satisfy high-level requirement.
- Providing manual gain and slope control to adjust suitable signals.

## **Specifications:**

- Operation Frequency Range: 40-860MHz. Single Directional network transmission, dedicated for the indoor CATV using.
- Output Level: 120dBuV
- ➤ Gain: Typical 40dB
- ➤ Gain Control: 0~20dB Continuously adjustable
- ➤ Tilt Control: 0~18dB Continuously adjustable
- ➤ Gain Flatness: ±2dB
- ➤ Noise Figure: <6dB
- ightharpoonup Input and Output Impedance: 75 $\Omega$
- Input and Output Test Point: 20dB
- Connector: Input and Output Test Points (All F-Type)
- ➤ Power Supply: 220V Ac
- Power Consumption: 8W
- ➤ Operating Temperature: -10~50′C
- > AC Fuse(Internal): 0.5 AMP
- ➤ Package: 1 pcs in a small box, and then a few in carton. We can also pack according to customer requirement
- > Can produce base on customer's requirement.